



charakterystyka									opakowanie - ilość szt.		masa jedn.	nr kat.
L	G	H	K	F	D <sub>1</sub>	D <sub>2</sub>	S	oring	woreczek	karton	kg	
35	1/2"	17	6	12,5	9,5	15	22	-	10	150	0,03	1637
50	1/2"	17	6	12,5	9,5	15	22	-	10	160	0,04	1638
70	1/2"	17	6	12,5	9,5	15	22	-	10	120	0,04	1639
100	1/2"	17	6	12,5	9,5	15	22	-	10	80	0,05	1640
35	1/2"	14	6	12,5	9,5	15	24	■	10	150	0,03	1646
50	1/2"	14	6	12,5	9,5	15	24	■	10	160	0,04	01638
70	1/2"	14	6	12,5	9,5	15	24	■	10	120	0,04	01639
100	1/2"	14	6	12,5	9,5	15	24	■	10	80	0,05	01640

## Parametry pracy

**Max ciśnienie robocze:**  
1,0 MPa (10bar)  
**Max temperatura robocza:**  
+110°C

## Materiały

CW617N

## Atesty i certyfikaty



Atest Higieniczny Narodowego Instytutu Zdrowia Publicznego  
BK/W/0734/01/2018



PN-EN ISO 9001:2015