



| charakterystyka | | | | | | | | | opakowanie - ilość szt. | | masa jedn. | nr kat. |
|-----------------|------|------|----|----|----|----------------|----------------|----------------|-------------------------|--------|------------|---------|
| G | R | L | h | k | Ø | S ₁ | S ₂ | S ₃ | woreczek | karton | kg | |
| 3/8" | 3/8" | 38 | 9 | - | - | 21 | 24 | 10 | 10 | 120 | 0,06 | 0358 |
| 1/2" | 1/2" | 43,5 | 14 | - | - | 24 | 30 | 13 | 10 | 40 | 0,11 | 0141 |
| 3/4" | 3/4" | 49 | 14 | - | - | 32 | 37 | 17 | 10 | 60 | 0,18 | 0142 |
| 1" | 1" | 57,5 | 14 | 19 | 25 | 38 | 45 | - | 5 | 30 | 0,28 | 0143 |
| 5/4" | 5/4" | 63 | 14 | 26 | 32 | 47 | 54 | - | 5 | 15 | 0,42 | 0356 |
| 3/2" | 3/2" | 70 | 14 | 33 | 39 | 54 | 60 | - | - | 15 | 0,52 | 0357 |
| 2" | 2" | 84 | 14 | 46 | 51 | 68 | 82 | - | - | 4 | 1,22 | 0395 |

Parametry pracy

Max ciśnienie robocze:
1,0 MPa (10bar)
Max temperatura robocza:
+110°C

Materiały

Króciec łącznika:
CW617N
Nakrętka łącznika:
CW617N
Uszczelnienie:
uszczelka fibrowa (F) / uszczelka gumowa (G)

Atesty i certyfikaty



Atest Higieniczny Narodowego Instytutu Zdrowia Publicznego
BK/W/0734/01/2018



PN-EN ISO 9001:2015