



charakterystyka						opakowanie - ilość szt.		masa jedn.	nr kat.
G1	G2	L	h <sub>1</sub>	h <sub>2</sub>	S	woreczek	karton	kg	
1/4"	3/8"	16	8	9	17	10	400	0,02	0255
M12x1,5	1/2"	17	8	8	21	10	200	0,03	0026
1/4"	1/2"	17	8	9	21	10	200	0,03	0027
3/8"	1/2"	17	9	9	21	10	200	0,03	0028
1/2"	3/4"	18	10	10	27	10	200	0,04	0030
1/2"	1"	21	10	12	34	5	80	0,08	0032
3/4"	1"	21	11	13	34	5	80	0,07	0033
3/4"	5/4"	26	12	13	38	5	50	0,12	0280
1"	5/4"	18	15	13	45	5	60	0,086	0505
5/4"	2"	32	17	19	60	-	36	0,32	1163
1/2"	6/4"	28	8	15	47	-	30	0,22	1266
1"	6/4"	28	13	15	47	-	64	0,14	001169
5/4"	6/4"	28	14	15	47	-	50	0,12	0035
6/4"	2"	32	19	19	60	-	36	0,27	1162
1"	2"	32	19	19	60	-	50	0,20	000259

## Parametry pracy

**Max ciśnienie robocze:**  
1,0 MPa (10bar)  
**Max temperatura robocza:**  
+150°C

## Materiały

CW617N

## Atesty i certyfikaty



Atest Higieniczny Narodowego Instytutu Zdrowia Publicznego  
HK/W/0530/01/2013

