



charakterystyka												opakowanie - ilość szt.		masa jedn.	nr kat.
G	L	K	F	D ₁	D ₂	D ₃	D ₄	S ₁	S ₂	S ₃	woreczek	karton	kg		
3/4"	121	65	69	18	10	18	6	27	14	14	5	20	0,300	9090014	
3/4"	121	65	69	22	10	18	6	32	14	14	5	20	0,330	9090015	
-	121	65	62	18	10	18	6	27	14	14	5	20	0,310	9090039	
-	121	65	62	22	10	22	6	32	14	14	5	20	0,340	9090016	
1/2"	171	65	69	18	10	18	6	27	14	14	5	15	0,280	90900145	
1/2"	171	65	69	22	10	18	6	32	14	14	5	15	0,290	90900155	
-	171	65	62	18	10	18	6	27	14	14	5	15	0,320	90900395	
-	171	65	62	22	10	22	6	32	14	14	5	15	0,340	90900165	
1/2"	221	65	69	18	10	18	6	27	14	14	5	15	0,290	90900142	
1/2"	221	65	69	22	10	18	6	32	14	14	5	15	0,300	90900152	
-	221	65	62	18	10	18	6	27	14	14	5	15	0,330	90900392	
-	221	65	62	22	10	22	6	32	14	14	5	15	0,250	90900162	

Parametry pracy

Max ciśnienie robocze:
1,0 MPa (10bar)
Max temperatura robocza:
+150°C

Materiały

Krzyż:
CW617N
Pierścień:
CW617N
Nakrętki:
CW617N
Tuleja zanurzeniowa:
CW617N
Odpowietrznik:
CW617N

Atesty i certyfikaty



Atest Higieniczny Narodowego Instytutu Zdrowia Publicznego
HK/W/0530/01/2013

