



charakterystyka							opakowanie - ilość szt.		masa jedn.	nr kat.
G	L	D <sub>1</sub>	D <sub>2</sub>	k	h	S	woreczek	karton	kg	
1/8"	35	3,2	6	20	9	14	10	150	0,013	90140N
1/4"	33	3,2	6	20	9	14	10	150	0,013	90141N
1/4"	35	5	8	20	9	14	10	150	0,016	90142N
1/4"	35	7	10	20	9	14	10	150	0,016	90143N
1/4"	35	9	12	20	9	14	10	150	0,016	90144N
3/8"	37	3,5	6	20	10	17	10	150	0,023	90146N
3/8"	37	5	8	20	10	17	10	150	0,025	90149N
3/8"	41	6,5	10	24	10	17	10	150	0,029	90150N
3/8"	41	8	12	24	10	17	10	150	0,031	90151N
3/8"	41	10	16	24	10	17	10	150	0,041	90152N
1/2"	43	6	10	24	11	22	10	100	0,040	90153N
1/2"	43	8,5	12	24	11	22	10	100	0,040	90154N
1/2"	43	12	16	25	11	22	10	100	0,041	90155N

## Parametry pracy

**Max ciśnienie robocze:**  
1,0 MPa (10bar)  
**Max temperatura robocza:**  
+95°C

## Materiały

CW617N

## Atesty i certyfikaty



Atest Higieniczny Narodowego Instytutu Zdrowia Publicznego  
HK/W/0530/01/2013

